



REGLOPLAS 

350LD

The temperature control unit for thermal oil up to 350 °C: 350LD

- Leak-free pump with magnetic coupling
- Microprocessor-controlled control system RT100
- Swiss Quality



Technical data

Outlet temperature

max.	°C	350
------	----	-----

Heat transfer fluid

Oil

Filling quantity	l	24
------------------	---	----

Expansion volume	l	20
------------------	---	----

Heating capacity at 400 V

Standard	kW	20
----------	----	----

Cooling capacity

Cooler type		1K
-------------	--	----

max.	kW	120
------	----	-----

Cooler type		2K
-------------	--	----

max.	kW	160
------	----	-----

at outlet temperature	°C	300
-----------------------	----	-----

Pump capacity

Type		FM65
------	--	------

Flow rate max.	l/min	90
----------------	-------	----

Pressure max.	bar	10
---------------	-----	----

Power consumption	kW	2,8
-------------------	----	-----

Control

Type		RT100
------	--	-------

Measuring mode		Pt100
----------------	--	-------

Operating voltage

Standard	V/Hz	400/50 3PE
----------	------	------------

Connections

Outlet/inlet		G3/4" IG
--------------	--	----------

Cooling water supply		G3/4"
----------------------	--	-------

Dimensions

Width	mm	546
-------	----	-----

Height	mm	1627
--------	----	------

Depth	mm	1466
-------	----	------

Weight

Standard	kg	373
----------	----	-----

Colour

Standard	RAL	9006/7016
----------	-----	-----------

Ambient temperature

max.	°C	40
------	----	----

Noise level

max.	db (A)	70
------	--------	----

Equipment

RT100 control system	●
----------------------	---

RT34 control system	—
---------------------	---

Unit in IP54 protection degree	●
--------------------------------	---

Second level	—
--------------	---

Leak-free pump	●
----------------	---

Filter in the main circuit	●
----------------------------	---

Filter in the cooling water circuit	●
-------------------------------------	---

Water circuit of non-rusting materials	●
----------------------------------------	---

Pressure gauge outlet	●
-----------------------	---

Pressure gauge inlet	●
----------------------	---

Inert gas blanket	○
-------------------	---

Bypass cooler 2K	○
------------------	---

Electronic flow measurement	○
-----------------------------	---

Solid-state relay (SSR) instead of heating contactor	●
------------------------------------------------------	---

● Standard ○ Option — Not available ● / ○ / — Device-related